

Application/Control Number: 10/640,341

Page 2

Art Unit: \*\*\*

CImpto

June 17, 2005

C.P.

BEST AVAILABLE COPY

Art Unit: \*\*\*

Claim 1 (currently amended): A surface light source device, comprising:  
a transparent light guide plate; plate;  
at least a light source for emitting light, positioned adjacent to a  
corresponding edge surface of the light guide plate; and  
~~at least a light source holder for fixing the light source;~~ light source holders  
provided at corners of the light guide plate for fixing the light source;  
wherein, ~~the at least a light source holder~~ the light source holders and the  
light guide plate combine into one assembly.

Claim 2 (currently amended): The surface light source device as described in  
claim 1, wherein ~~the at least a light source holder is~~ the light source holders are  
made of silicon rubber.

Claim 3 (currently amended): The surface light source device as described in  
claim 1, wherein ~~the at least a light source holder is~~ the light source holders are  
integrated with the light guide plate by an injection-molding process.

Claim 4 (currently amended): The surface light source device as described in  
claim 1, wherein ~~the at least a light source holder is~~ the light source holders are  
attached to the light guide plate.

Art Unit: \*\*\*

Claim 5 (canceled)

Claim 6 (currently amended): The surface light source device as described in claim 1, further comprising at least a reflector coupling with ~~at least a light source holder~~ the light source holders and enclosing a corresponding light source on three sides.

Claim 7 (currently amended): The surface light source device as described in claim 6, wherein the reflector has at least a protrusion for engaging with at least an edge of ~~at least one of the corresponding light source holders~~.

Claim 8 (original): The surface light source device as described in claim 6, wherein the reflector is attached to the corresponding light source holders using screws or by bonding.

Claim 9 (currently amended): The surface light source device as described in claim 1, wherein ~~the at least a light source holder~~ each light source holder has a hole for receiving an end of the ~~at least a~~ light source.

Claim 10 (currently amended): The surface light source device as described in claim 9, wherein a heat insulated spacer is installed between an inner surface of each hole and a corresponding end of the corresponding light source, and an inner diameter of the heat insulated spacer is slightly greater than a diameter of the end of the light source, and a diameter of the hole is slightly greater than an outer diameter of the heat insulated spacer.

Claim 11 (currently amended): A surface light source device, comprising:

Art Unit: \*\*\*

a transparent light guide ~~plate~~; plate;

at least a light source for emitting light, positioned adjacent to a corresponding edge surface of the light guide plate; and

~~at least a light source holder for fixing the light source~~; a plurality of light source holders, each light source holder being provided at a respective corner of the light guide plate;

wherein, the ~~at least a light source holder is~~ light source holders are integrally formed with the light guide plate by an injection-molding process.

Claim 12 (currently amended): The surface light source device as described in claim 11, wherein ~~the at least a light source holder is~~ the light source holders are made of silicon rubber.

Claim 13 (canceled)

Claim 14 (currently amended): The surface light source device as described in claim ~~[[13]]~~ 11, wherein each light source holder has a hole for receiving a corresponding end of a corresponding light source.

Claim 15 (currently amended): The surface light source device as described in claim 14, wherein a heat insulated spacer is installed between an inner surface of each hole and a corresponding end of the corresponding light source, ~~and~~ an inner diameter of the heat insulated spacer is slightly greater than a diameter of the end of the light source, and a diameter of the hole is slightly greater than an outer diameter of the heat insulated spacer.

Claim 16 (currently amended): The surface light source device as described in claim 11, further comprising at least a reflector coupling with ~~at least a light source~~

Art Unit: \*\*\*

~~holder~~ the light source holders and enclosing a corresponding light source on three sides.

Claim 17 (currently amended): The surface light source device as described in claim 16, wherein the reflector has at least a protrusion for engaging with at least an edge of ~~at least~~ one of the corresponding light source holders.

Claim 18 (original): The surface light source device as described in claim 16, wherein the reflector is attached to the corresponding light source holders using screws or by bonding.

Claims 19-24 cancelled

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINE(S) OR MARK(S) ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**